



Safety Data Sheet

Spartan Chemical Company, Inc.

Revision Date: 11-Dec-2017

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name: RINSE FREE STRIP
Product Number: 0082
Recommended Use: Stripping solution
Uses Advised Against: For Industrial and Institutional Use Only

Manufacturer/Supplier: Spartan Chemical Company, Inc.
1110 Spartan Drive
Maumee, Ohio 43537 USA
800-537-8990 (Business hours)
www.spartanchemical.com

24 Hour Emergency Phone Numbers:

Medical Emergency/Information: 888-314-6171
Transportation/Spill/Leak: CHEMTREC 800-424-9300

2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity - Inhalation (Vapors) Category 4
Skin Corrosion/Irritation: Category 1
Serious Eye Damage/Eye Irritation: Category 1

GHS Label Elements

Signal Word:

Symbols:

Danger



Hazard Statements:

Harmful if inhaled.
Causes severe skin burns and serious eye damage.

Precautionary Statements:

Prevention:

Use only outdoors or in a well-ventilated area
Do not breathe mist, vapors or spray.
Wash hands and any exposed skin thoroughly after handling.
Wear protective gloves. Wear eye / face protection. Wear protective clothing.

Response:

IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

-Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

-Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse.

-Inhalation:

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

-Ingestion:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

-Specific Treatment:

See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.

Storage:

Store locked up.

Disposal:

Dispose of contents and container in accordance with local, state and federal regulations.

Hazards Not Otherwise Classified: Not Applicable

Other Information:

- Harmful if swallowed
- Harmful contact may not cause immediate pain.
- Harmful if absorbed through skin.
- Inhalation of vapors or mist may cause respiratory irritation or damage.
- Keep out of reach of children.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Chemical Name | CAS No | Weight-% |
|-----------------------------------|-----------|----------|
| water | 7732-18-5 | 60-100 |
| 2-butoxyethanol | 111-76-2 | 10-30 |
| propylene glycol monomethyl ether | 107-98-2 | 1-5 |
| monoethanolamine | 141-43-5 | 1-5 |

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

-Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

-Skin Contact: Take off immediately all contaminated clothing and shoes. Rinse with water or shower for at least 15 minutes. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Wash contaminated clothing before reuse. Discard or destroy contaminated shoes.

-Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Call a poison control center or physician if you feel unwell.

-Ingestion: Rinse mouth. Do NOT induce vomiting. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Never give anything by mouth to an unconscious person.

Note to Physicians: Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Use, Dry chemical, Carbon dioxide, Water spray (fog), Alcohol resistant foam

Specific Hazards Arising from the Chemical: Dried product is capable of burning. Combustion products are toxic.

Hazardous Combustion Products: May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.

Protective Equipment and Precautions for Firefighters: Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear. Cool fire-exposed containers with water spray.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

Environmental Precautions: Do not rinse spill onto the ground, into storm sewers or bodies of water.

Methods for Clean-Up: Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

7. HANDLING AND STORAGE

Advice on Safe Handling: Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling. Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

Storage Conditions: Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Keep from freezing.

Suggested Shelf Life: Minimum of 2 years from date of manufacture.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational Exposure Limits:

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH |
|---|------------------------------|---|---|
| 2-butoxyethanol 111-76-2 | TWA: 20 ppm | TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S* S* | IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³ |
| propylene glycol monomethyl ether 107-98-2 | STEL: 100 ppm TWA: 50 ppm | (vacated) TWA: 100 ppm (vacated) TWA: 360 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 540 mg/m ³ | TWA: 100 ppm TWA: 360 mg/m ³ STEL: 150 ppm STEL: 540 mg/m ³ |
| monoethanolamine 141-43-5 | STEL: 6 ppm TWA: 3 ppm | TWA: 3 ppm TWA: 6 mg/m ³ (vacated) TWA: 3 ppm (vacated) TWA: 8 mg/m ³ (vacated) STEL: 6 ppm (vacated) STEL: 15 mg/m ³ | IDLH: 30 ppm TWA: 3 ppm TWA: 8 mg/m ³ STEL: 6 ppm STEL: 15 mg/m ³ |

Engineering Controls: Provide good general ventilation.
If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other engineering controls should be considered.
Eye wash stations and shower facilities should be readily accessible in areas where the product is handled.

Personal Protective Equipment

Eye/Face Protection:

Wear splash goggles. For severe use-conditions, wear a face shield over the goggles.

Skin and Body Protection:

Wear rubber or other chemical-resistant gloves and solvent / alkali resistant boots. The use of other protective equipment should be considered in order to prevent or minimize contact with this product.

Respiratory Protection:

Not required with expected use.

If occupational exposure limits are exceeded or respiratory irritation occurs, use of a NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section 3 should be considered.

General Hygiene Considerations:

Wash hands and any exposed skin thoroughly after handling.
See 29 CFR 1910.132-138 for further guidance.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|-----------------------------|
| Appearance/Physical State: | Liquid |
| Color: | Clear |
| Odor: | Mint fragrance |
| pH: | 11.8-12.4 |
| Melting Point / Freezing Point: | No information available. |
| Boiling Point / Boiling Range: | 94 °C / 201 °F |
| Flash Point: | > 94 °C / > 201 °F ASTM D56 |
| Evaporation Rate: | < 1 (Butyl acetate = 1) |
| Flammability (solid, gas) | No information available. |
| Upper Flammability Limit: | No information available. |
| Lower Flammability Limit: | No information available. |
| Vapor Pressure: | No information available. |
| Vapor Density: | No information available. |
| Specific Gravity: | 0.997 |
| Solubility(ies): | Soluble in water |
| Partition Coefficient: | No information available. |
| Autoignition Temperature: | No information available. |
| Decomposition Temperature: | No information available. |
| Viscosity: | No information available. |

10. STABILITY AND REACTIVITY

| | |
|--|---|
| Reactivity: | This material is considered to be non-reactive under normal conditions of use. |
| Chemical Stability: | Stable under normal conditions. |
| Possibility of Hazardous Reactions: | Not expected to occur with normal handling and storage. |
| Conditions to Avoid: | Extremes of temperature and direct sunlight. |
| Incompatible Materials: | Strong oxidizing agents. Strong acids. |
| Hazardous Decomposition Products: | May include carbon monoxide, carbon dioxide (CO ₂) and other toxic gases or vapors. |

11. TOXICOLOGICAL INFORMATION

| | |
|--|--|
| Likely Routes of Exposure: | Eyes, Skin, Ingestion, Inhalation. |
| Symptoms of Exposure: | |
| -Eye Contact: | Pain, redness, swelling of the conjunctiva and tissue damage. Eye contact may cause permanent damage. |
| -Skin Contact: | Pain, redness, blistering and possible chemical burn. |
| -Inhalation: | Irritation or damage to the mucus membranes of the respiratory tract. Inhalation of vapors in high concentration may cause irritation of respiratory system. |
| -Ingestion: | Damage or chemical burns to mouth, throat and stomach. Pain, nausea, vomiting and diarrhea. |
| Immediate, Delayed, Chronic Effects | |
| Product Information: | Data not available or insufficient for classification. |
| Chronic Toxicity: | May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects. |
| Target Organ Effects: | Blood. Central nervous system. -Eyes. hematopoietic system. kidney. Liver. Respiratory System. -Skin. |
| Numerical Measures of Toxicity | |
| The following acute toxicity estimates (ATE) are calculated based on the GHS document. | |
| ATEmix (oral): | 2807 mg/kg |
| ATEmix (dermal): | 5462 mg/kg |
| ATEmix (inhalation-dust/mist): | 10.1 mg/l |
| ATEmix (inhalation-vapor): | 14.5 mg/l |

Component Acute Toxicity Information

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|---------------|-----------|-------------|-----------------|
| | | | |

| | | | |
|---|----------------------|-------------------------|------------------------|
| water 7732-18-5 | > 90 mL/kg (Rat) | Not Available | Not Available |
| 2-butoxyethanol 111-76-2 | = 470 mg/kg (Rat) | = 99 mg/kg (Rabbit) | = 450 ppm (Rat) 4 h |
| propylene glycol monomethyl ether 107-98-2 | = 5000 mg/kg (Rat) | = 13 g/kg (Rabbit) | > 7559 ppm (Rat) 6 h |
| monoethanolamine 141-43-5 | = 1720 mg/kg (Rat) | = 1000 mg/kg (Rabbit) | Not Available |

Carcinogenicity: No components present at 0.1% or greater are listed as to being carcinogens by ACGIH, IARC, NTP or OSHA.

12. ECOLOGICAL INFORMATION

Ecotoxicity

| Chemical Name | Algae/Aquatic Plants | Fish | Toxicity to Microorganisms | Crustacea |
|---|--|--|----------------------------|-------------------------------------|
| 2-butoxyethanol 111-76-2 | Not Available | 1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50 | Not Available | 1000: 48 h Daphnia magna mg/L EC50 |
| propylene glycol monomethyl ether 107-98-2 | Not Available | 20.8: 96 h Pimephales promelas g/L LC50 static | Not Available | 23300: 48 h Daphnia magna mg/L EC50 |
| monoethanolamine 141-43-5 | 15: 72 h Desmodesmus subspicatus mg/L EC50 | 227: 96 h Pimephales promelas mg/L LC50 flow-through 3684: 96 h Brachydanio rerio mg/L LC50 static 300 - 1000: 96 h Lepomis macrochirus mg/L LC50 static 114 - 196: 96 h Oncorhynchus mykiss mg/L LC50 static 200: 96 h Oncorhynchus mykiss mg/L LC50 flow-through | Not Available | 65: 48 h Daphnia magna mg/L EC50 |

Persistence and Degradability: No information available.

Bioaccumulation: No information available.

Other Adverse Effects: No information available.

13. DISPOSAL CONSIDERATIONS

Disposal of Wastes: Dispose of in accordance with federal, state and local regulations.

Contaminated Packaging: Dispose of in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

DOT: Not Regulated

Proper Shipping Name: Non-Hazardous Product

Special Provisions: Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Check with a trained hazardous materials transportation expert for information specific to your situation.

IMDG: Not Regulated

Proper Shipping Name: Non-Hazardous Product

15. REGULATORY INFORMATION

TSCA Status: (Toxic Substance Control Act Section 8(b) Inventory)

All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

SARA 313

This product contains the following listed substances:

2-butoxyethanol

CAS No 111-76-2 applies to R-(OCH₂CH₂)_n-OR', where n = 1, 2, or 3, R=Alkyl C7 or less, or R = Phenyl or Alkyl substituted phenyl, R' = H or Alkyl C7 or less, or OR' consisting of Carboxylic acid ester, Sulfate, Phosphate, Nitrate, or Sulfonate
Chemical Category N230

SARA 311/312 Hazard Categories

| | |
|------------------------------------|-----|
| Acute Health Hazard: | Yes |
| Chronic Health Hazard: | No |
| Fire Hazard: | Yes |
| Sudden release of pressure hazard: | No |
| Reactive Hazard: | No |

California Proposition 65

This product is not subject to warning requirements under California Proposition 65.

16. OTHER INFORMATION

| | | | | |
|-------------|---------------------------|------------------------|----------------------------|---------------------|
| NFPA | Health Hazards: 2 | Flammability: 0 | Instability: 0 | Special: N/A |
| HMIS | Health Hazards: 2* | Flammability: 0 | Physical Hazards: 0 | |

Revision Date: 11-Dec-2017
Reasons for Revision: Section 7 and 9

Disclaimer:

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet