

Safety Data Sheet Spartan Chemical Company, Inc.

Revision Date: 20-Jan-2017

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name: XTREME BUG BLASTER PRE-SPRAY

Product Number: 2666

Recommended Use: Cleaning agent

Uses Advised Against: For Industrial and Institutional Use Only

Manufacturer/Supplier: Spartan Chemical Company, Inc.

1110 Spartan Drive

Maumee, Ohio 43537 USA 800-537-8990 (Business hours) www.spartanchemical.com

24 Hour Emergency Phone Numbers:

Medical Emergency/Information: 888-314-6171

Transportation/Spill/Leak: CHEMTREC 800-424-9300

2. HAZARDS IDENTIFICATION

GHS Classification

Skin Corrosion/Irritation: Category 1 Sub-category B

Serious Eye Damage/Eye Irritation: Category 1 Corrosive to Metals: Category 1

GHS Label Elements

Signal Word: Danger

Symbols:

Hazard Statements: Causes severe skin burns and serious eye damage.

May be corrosive to metals.

Precautionary Statements:

Prevention: Do not breathe mist, vapors or spray.

Wash hands and any exposed skin thoroughly after handling.

Wear protective gloves. Wear eye / face protection. Wear protective clothing.

Keep in original or other corrosion resistant container.

Response: IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

-Eyes IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

-Skin IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

or shower. Wash contaminated clothing before reuse.

-Inhalation: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

-Ingestion: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

-Specific Treatment: See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.

Spill: Absorb spillage to prevent material damage.

Storage: Store locked up. Store in corrosion resistant container.

Disposal: Dispose of contents and container in accordance with local, state and federal regulations.

Hazards Not Otherwise Classified: Not Applicable

Other Information: · Corrosive.

· Harmful if swallowed

Harmful contact may not cause immediate pain.

• Inhalation of vapors or mist may cause respiratory irritation.

Keep out of reach of children.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric

Revision Date: 20-Jan-2017

lavage.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Chemical Name | CAS No | Weight-% |
|------------------------------|------------|----------|
| water | 7732-18-5 | 60-100 |
| potassium hydroxide | 1310-58-3 | 1-5 |
| ethoxylated alkyl quaternary | 61791-10-4 | 1-5 |
| 2-butoxyethanol | 111-76-2 | 1-5 |
| sodium laureth sulfate | 9004-82-4 | 1-5 |
| alcohol ethoxylate | 68439-46-3 | 1-5 |

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

-Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Take off immediately all contaminated clothing and shoes. Rinse with water or shower for -Skin Contact:

at least 15 minutes. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

Remove victim to fresh air and keep at rest in a position comfortable for breathing. -Inhalation:

IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

Rinse mouth. Do NOT induce vomiting. IMMEDIATELY CALL A POISON CENTER OR -Ingestion:

PHYSICIAN.

Note to Physicians: NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric

lavage.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Product does not support combustion, Use extinguishing agent suitable for type of

surrounding fire

Specific Hazards Arising from the

Chemical:

Dried product is capable of burning. Combustion products are toxic.

Hazardous Combustion Products: May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.

Protective Equipment and Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full **Precautions for Firefighters:**

protective gear. Cool fire-exposed containers with water spray.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Environmental Precautions: Methods for Clean-Up:

Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Do not rinse spill onto the ground, into storm sewers or bodies of water.

Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

7. HANDLING AND STORAGE

Advice on Safe Handling: Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly

after handling.

Storage Conditions: Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach

of children. Keep from freezing.

Incompatible Materials: Strong acids. Reactive metals such as aluminum, zinc and tin.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational Exposure Limits:

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH |
|----------------------------------|------------------------------|---|--|
| potassium hydroxide 1310-58-3 | Ceiling: 2 mg/m ³ | (vacated) Ceiling: 2 mg/m ³ | Ceiling: 2 mg/m ³ |
| 2-butoxyethanol 111-76-2 | TWA: 20 ppm | TWA: 50 ppm TWA: 240 mg/m³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m³ (vacated) S* S* | IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m³ |

Engineering Controls: Provide good general ventilation.

If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other

Revision Date: 20-Jan-2017

engineering controls should be considered.

Eye wash stations and shower facilities should be readily accessible in areas where the

product is handled.

Personal Protective Equipment

Eye/Face Protection: Skin and Body Protection: Wear splash goggles. For severe use-conditions, wear a face shield over the goggles. Wear rubber or other chemical-resistant gloves. Use of impervious apron, boots and other protective equipment should be considered in order to prevent or minimize contact with this

product.

Respiratory Protection: Not required with expected use.

If occupational exposure limits are exceeded or respiratory irritation occurs, use of a NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section

3 should be considered.

General Hygiene Considerations: Wash hands and any exposed skin thoroughly after handling.

See 29 CFR 1910.132-138 for further guidance.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | h | |
|---------------------------------|------------------------------|--|
| Appearance/Physical State: | Liquid | |
| Color: | Neon Yellow | |
| Odor: | solvent | |
| pH: | 13.5-14.00 | |
| Melting Point / Freezing Point: | No information available. | |
| Boiling Point / Boiling Range: | 100 °C / 212 °F | |
| Flash Point: | > 100 °C / > 212 °F ASTM D56 | |
| Evaporation Rate: | < 1.0 (Butyl acetate = 1) | |
| Flammability (solid, gas) | No information available. | |
| Upper Flammability Limit: | No information available. | |
| Lower Flammability Limit: | No information available. | |
| Vapor Pressure: | No information available. | |
| Vapor Density: | No information available. | |
| Specific Gravity: | 1.042 | |
| Solubility(ies): | Soluble in water | |
| Partition Coefficient: | No information available. | |
| Autoignition Temperature: | No information available. | |
| Decomposition Temperature: | No information available. | |
| Viscosity: | No information available. | |

10. STABILITY AND REACTIVITY

Revision Date: 20-Jan-2017

Reactivity: This material is considered to be non-reactive under normal conditions of use.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Contact with aluminum or other reactive metals may release hydrogen gas.

Conditions to Avoid: Extremes of temperature and direct sunlight.

Incompatible Materials: Strong acids. Reactive metals such as aluminum, zinc and tin.

Hazardous Decomposition Thermal decomposition can lead to release of irritating and toxic gases and vapors

Products:

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Eyes, Skin, Ingestion, Inhalation.

Symptoms of Exposure:

-Eye Contact: Pain, redness, swelling of the conjunctiva and tissue damage. Eye contact may cause

permanent damage.

-Skin Contact: Pain, redness, blistering and possible chemical burn.

-Inhalation: Irritation or damage to the mucus membranes of the respiratory tract. Nasal discomfort and

coughing.

-Ingestion: Damage or chemical burns to mouth, throat and stomach. Pain, nausea, vomiting and

diarrhea.

Immediate, Delayed, Chronic Effects

Product Information: Data not available or insufficient for classification.

Target Organ Effects: Blood. Central nervous system. -Eyes. hematopoietic system. kidney. Liver. Respiratory

System. -Skin.

Numerical Measures of Toxicity

The following acute toxicity estimates (ATE) are calculated based on the GHS document.

ATEmix (oral): 3955 mg/kg
ATEmix (dermal): 26776 mg/kg
ATEmix (inhalation-dust/mist): 49.9 mg/l
ATEmix (inhalation-vapor): 366 mg/l

Component Acute Toxicity Information

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 | |
|--|---------------------|---|--|--|
| water 7732-18-5 | > 90 mL/kg (Rat) | Not Available | Not Available | |
| potassium hydroxide 1310-58-3 | = 214 mg/kg (Rat) | Not Available | Not Available | |
| ethoxylated alkyl quaternary 61791-10-4 | = 580 mg/kg (Rat) | Not Available | Not Available | |
| 2-butoxyethanol 111-76-2 | = 470 mg/kg (Rat) | = 2270 mg/kg (Rat) = 220 mg/kg (Rabbit) | = 2.21 mg/L (Rat)4 h = 450 ppm (Rat)4 h | |
| sodium laureth sulfate 9004-82-4 | = 1600 mg/kg (Rat) | Not Available | Not Available | |
| alcohol ethoxylate 68439-46-3 | = 1378 mg/kg (Rat) | > 2 g/kg (Rabbit) | Not Available | |

Carcinogenicity: No components present at 0.1% or greater are listed as to being carcinogens by ACGIH, IARC, NTP or OSHA.

12. ECOLOGICAL INFORMATION

Ecotoxicity

| Chemical Name | Algae/Aquatic Plants | Fish | Toxicity to Microorganisms | Crustacea |
|----------------------------------|----------------------|---|----------------------------|---|
| potassium hydroxide 1310-58-3 | Not Available | 80: 96 h Gambusia affinis mg/L LC50 static | Not Available | Not Available |
| 2-butoxyethanol 111-76-2 | Not Available | 1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50 | Not Available | 1698 - 1940: 24 h Daphnia magna mg/L EC50 1000: 48 h Daphnia magna mg/L EC50 |

Persistence and Degradability:

Bioaccumulation:

No information available.

No information available.

Other Adverse Effects: No information available.

13. DISPOSAL CONSIDERATIONS

Disposal of Wastes:Dispose of in accordance with federal, state and local regulations.
Contaminated Packaging:
Dispose of in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

DOT: Regulated UN/ID No: UN1760

Proper Shipping Name: Corrosive liquids, n.o.s., (contains potassium hydroxide)

Hazard Class: 8
Packing Group: II

Special Provisions: Shipping descriptions may vary based on mode of transport, quantities, package size,

and/or origin and destination. Check with a trained hazardous materials transportation

Revision Date: 20-Jan-2017

expert for information specific to your situation.

UN/ID No: UN1760

Proper Shipping Name: Corrosive liquids, n.o.s., (contains potassium hydroxide)

Hazard Class: 8
Packing Group: ||

15. REGULATORY INFORMATION

TSCA Status: (Toxic Substance Control Act Section 8(b) Inventory)

All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

SARA 313

This product contains the following listed substances:

2-butoxyethanol

CAS No 111-76-2 applies to R-(OCH2CH2)n-OR', where n = 1, 2, or 3, R=Alkyl C7 or less, or R = Phenyl or Alkyl substituted phenyl, R' = H or Alkyl C7 or less, or OR' consisting of Carboxylic acid ester, Sulfate, Phosphate, Nitrate, or Sulfonate, Chemical Category N230

SARA 311/312 Hazard Categories

Acute Health Hazard:

Chronic Health Hazard:

Fire Hazard:

Sudden release of pressure hazard:

No
Reactive Hazard:

No

California Proposition 65

This product is not subject to warning requirements under California Proposition 65.

16. OTHER INFORMATION

NFPA Health Hazards: 3 Flammability: 0 Instability: 0 Special: N/A

HMIS Health Hazards: 3* Flammability: 0 Physical Hazards: 0

Revision Date: 20-Jan-2017 **Reasons for Revision:** New product

Revision Date: 20-Jan-2017

Disclaimer:

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet