

# Safety Data Sheet Spartan Chemical Company, Inc.

Revision Date: 11-Aug-2015

# 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Identifier** 

Product Name: FOOD GRADE MACHINERY LUBRICANT

Product Number: 6525
Recommended Use: Lubricant

Uses Advised Against: For Industrial and Institutional Use Only

Manufacturer/Supplier: Spartan Chemical Company, Inc.

1110 Spartan Drive Maumee, Ohio 43537 USA 800-537-8990 (Business hours) www.spartanchemical.com

24 Hour Emergency Phone Numbers:

Medical Emergency/Information: 888-314-6171

Transportation/Spill/Leak: CHEMTREC 800-424-9300

#### 2. HAZARDS IDENTIFICATION

**GHS Classification** 

Aspiration Toxicity: Category 1
Flammable Aerosols Category 1
Gases Under Pressure Liquefied gas

**GHS Label Elements** 

Signal Word:

Symbols:

Danger



Hazard Statements: May be fatal if swallowed and enters airways

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated

**Precautionary Statements:** 

**Prevention:** Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

fatal.

Response:

-Ingestion: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT

induce vomiting.

-Specific Treatment: See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.

Storage: Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 122°F

(50°C) Store in a well-ventilated place

**Disposal:** Dispose of contents and container in accordance with local, state and federal regulations.

Hazards Not Otherwise Classified: Not Applicable

Other Information: May be harmful if swallowed.

· May cause eye irritation.

• Inhalation of vapors or mist may cause respiratory irritation.

Revision Date: 11-Aug-2015

· Keep out of reach of children.

· Contains petroleum distillates. Possible aspiration hazard.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
white mineral oil	8042-47-5	60-100
N-butane	106-97-8	10-30
propane	74-98-6	5-10

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

-Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

> easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Wash with soap and water. If skin irritation occurs: Get medical attention.

-Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a

poison control center or physician if you feel unwell.

IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Do NOT induce vomiting. -Ingestion:

Never give anything by mouth to an unconscious person. Contains petroleum distillates. Possible aspiration hazard.

#### 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Water spray (fog), Foam

Specific Hazards Arising from the

Chemical:

Extremely flammable aerosol. Exposure to high temperature may cause containers to burst. Bursting aerosol containers may be propelled from fire at high speed.

**Hazardous Combustion Products:** May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.

**Protective Equipment and** 

Note to Physicians:

-Skin Contact:

**Precautions for Firefighters:** 

Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear. Water may be used to cool closed containers to prevent pressure build-up

and possible auto ignition or explosion when exposed to extreme heat.

#### 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions: Environmental Precautions: Methods for Clean-Up:** 

Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

Do not rinse spill onto the ground, into storm sewers or bodies of water.

Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

#### 7. HANDLING AND STORAGE

Advice on Safe Handling: Handle in accordance with good industrial hygiene and safety practice. Intentional misuse

by deliberately concentrating and inhaling contents may be harmful or fatal. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Wash thoroughly after

handling.

**Storage Conditions:** NFPA 30B Level 3 Aerosol. Do not store in direct sunlight or above 122 F° / 50 C°.

Exposure to high temperature may cause containers to burst. Keep out of the reach of

children.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Occupational Exposure Limits:** 

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH
N-butane 106-97-8	TWA: 1000 ppm	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup>
propane 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m³ (vacated) TWA: 1800 mg/m³ (vacated) TWA: 1800 mg/m³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>

**Engineering Controls:** Provide good general ventilation.

If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other engineering controls should be considered.

Revision Date: 11-Aug-2015

Personal Protective Equipment

Eye/Face Protection:
Skin and Body Protection:
Respiratory Protection:

Not required with expected use. Not required with expected use. Not required with expected use.

If occupational exposure limits are exceeded or respiratory irritation occurs, use of a NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section

3 should be considered.

**General Hygiene Considerations:** 

Wash hands and any exposed skin thoroughly after handling.

See 29 CFR 1910.132-138 for further guidance.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical State:	Aerosol		
Color:	Colorless		
Odor:	Odorless		
pH:	Not applicable		
Melting Point / Freezing Point:	No information available.		
Boiling Point / Boiling Range:	> 271 °C / 520 °F (Product without propellant)		
Flash Point:	< -18 °C / < 0 °F (Propellant-estimated)		
Evaporation Rate:	< 1 (Butyl acetate = 1)		
Flammability (solid, gas)	No information available.		
Upper Flammability Limit:	No information available.		
Lower Flammability Limit:	No information available.		
Vapor Pressure:	No information available.		
Vapor Density:	No information available.		
Specific Gravity:	0.81 0.81-0.87 (Product without propellant)		
Solubility(ies):	No information available. Insoluble		
Partition Coefficient:	No information available.		
Autoignition Temperature:	No information available.		
Decomposition Temperature:	No information available.		
Viscosity:	No information available.		

# 10. STABILITY AND REACTIVITY

**Reactivity:** This material is considered to be non-reactive under normal conditions of use.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Not expected to occur with normal handling and storage.

**Conditions to Avoid:** Extremes of temperature and direct sunlight. **Incompatible Materials:** Strong oxidizing agents. Strong acids.

Hazardous Decomposition May include carbon monoxide, carbon dioxide (CO2) and other toxic gases or vapors.

**Products:** 

# 11. TOXICOLOGICAL INFORMATION

Revision Date: 11-Aug-2015

**Likely Routes of Exposure:** Eyes, Skin, Ingestion, Inhalation.

Symptoms of Exposure:

-Eye Contact: Pain and redness. -Skin Contact: Drying of the skin.

**-Inhalation:** Nasal discomfort and coughing.

-Ingestion: Pain, nausea, vomiting and diarrhea. Aspiration may cause pulmonary edema and

pneumonitis.

Immediate, Delayed, Chronic Effects

Product Information: Data not available or insufficient for classification.

Target Organ Effects: Central nervous system.

**Numerical Measures of Toxicity** 

The following acute toxicity estimates (ATE) are calculated based on the GHS document.

ATEmix (oral): 6667 mg/kg ATEmix (inhalation-gas): 1208587 mg/l

**Component Acute Toxicity Information** 

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
white mineral oil	> 5000 mg/kg (Rat)	Not Available	Not Available
8042-47-5 N-butane	Not Available	Not Available	= 658 mg/L (Rat) 4 h
106-97-8			
propane 74-98-6	Not Available	Not Available	= 658 mg/L (Rat) 4 h

Carcinogenicity: No components present at 0.1% or greater are listed as to being carcinogens by ACGIH, IARC, NTP or OSHA.

#### 12. ECOLOGICAL INFORMATION

**Ecotoxicity** 

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
white mineral oil 8042-47-5	Not Available	10000: 96 h Lepomis macrochirus mg/L LC50	Not Available	Not Available

Persistence and Degradability:<br/>Bioaccumulation:No information available.<br/>No information available.Other Adverse Effects:No information available.

# 13. DISPOSAL CONSIDERATIONS

**Disposal of Wastes:** Dispose of in accordance with federal, state and local regulations.

Contaminated Packaging: Pressurized container: Do not pierce or burn, even after use. Dispose of in accordance with

federal, state and local regulations.

#### 14. TRANSPORT INFORMATION

DOT:

UN/ID No: UN1950
Proper Shipping Name: Aerosols
Hazard Class: 2.1

Special Provisions: This product meets the exception requirements of section 49 CFR 173.306 as a limited

quantity and may be shipped as a limited quantity.

IMDG:

UN/ID No: UN1950
Proper Shipping Name: Aerosols
Hazard Class: 2.1

Additional information: Limited Quantity

Revision Date: 11-Aug-2015

# 15. REGULATORY INFORMATION

TSCA Status: (Toxic Substance Control Act Section 8(b) Inventory)

All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

#### **SARA 313**

This product does not contain listed substances above the "de minimus" level

SARA 311/312 Hazard Categories

Acute Health Hazard:

Chronic Health Hazard:

Fire Hazard:

Sudden release of pressure hazard:

Reactive Hazard:

Yes

Yes

Yes

Yes

No

#### **California Proposition 65**

This product is not subject to warning requirements under California Proposition 65.

#### **16. OTHER INFORMATION**

NFPA Health Hazards: 1 Flammability: 3 Instability: 0 Special: N/A

Health Hazards: 1 Flammability: 4 Physical Hazards: 2

**Revision Date:** 11-Aug-2015 **Reasons for Revision:** Section 14 and 15

#### Disclaimer:

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**