



SAFETY DATA SHEET

Issue Date 29-Nov-2022

Revision Date 29-Nov-2022

Version 2

1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Product Name Oven & Grill Cleaner 70

Other means of identification

Product Code N-02019

Synonyms None

Details of the supplier of the safety data sheet

Company Name Nassco Inc.
5355 S. Westridge Drive
New Berlin, WI 53151
(800) 729-6726

Emergency telephone number

Emergency Telephone Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| | |
|-----------------------------------|------------|
| Skin corrosion/irritation | Category 1 |
| Serious eye damage/eye irritation | Category 1 |

Label elements

Emergency Overview

Danger

Hazard statements

Causes severe skin burns and eye damage



Appearance Clear Yellow

Physical state Liquid

Odor Lemon

Precautionary Statements - Prevention

Do not breathe dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

Specific Treatment (See Section 4 on the SDS)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Immediately call a POISON CENTER or doctor/physician

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Immediately call a POISON CENTER or doctor/physician

IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Disposal should be in accordance with applicable regional, national and local laws and regulations

Hazards not otherwise classified (HNOC)

Other Information

- Toxic to aquatic life with long lasting effects
- Toxic to aquatic life

Unknown Acute Toxicity

0.0633 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS No. | Weight-% | Trade Secret |
|---------------------------|-----------|----------|--------------|
| Potassium Hydroxide | 1310-58-3 | 1-5 | * |
| Tetrasodium EDTA | 64-02-8 | 1-5 | * |
| 2-(2-butoxyethoxy)ethanol | 112-34-5 | 1-5 | * |

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures

General advice

Immediate medical attention is required.

Skin Contact

Immediate medical attention is required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. For minor skin contact, avoid spreading material on unaffected skin. For severe burns, immediate medical attention is required.

Eye contact

Do not rub affected area. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician or poison control center immediately.

Ingestion

Rinse mouth. Drink plenty of water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Self-protection of the first aider

Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms

Any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed**Note to physicians**

Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. Treat symptomatically.

5. FIRE-FIGHTING MEASURES**Suitable extinguishing media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating and toxic gases and vapors. In the event of fire and/or explosion do not breathe fumes.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures****Personal precautions**

Avoid contact with skin, eyes or clothing. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Use personal protective equipment as required.

Environmental precautions**Environmental precautions**

Do not allow into any storm sewer drains, lakes, streams, ponds, estuaries, oceans or other surface water bodies. Should not be released into the environment. Dispose of according to all local city, state and federal rules and regulations.

Methods and material for containment and cleaning up**Methods for containment**

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Dam up. Dike far ahead of liquid spill for later disposal. Prevent product from entering drains. Soak up with inert absorbent material. Take up mechanically, placing in appropriate containers for disposal. Clean contaminated surface thoroughly. After cleaning, flush away traces with water.

7. HANDLING AND STORAGE**Precautions for safe handling****Advice on safe handling**

Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation, especially in confined areas. In case of insufficient ventilation, wear suitable respiratory equipment. Use only with adequate ventilation and in closed systems.

Conditions for safe storage, including any incompatibilities**Storage Conditions**

Keep out of the reach of children. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep in properly labeled containers.

Incompatible materials

Strong acids. Aluminum. Incompatible with strong acids and bases. Incompatible with

oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|---------------------------------------|---|---|---|
| Potassium Hydroxide 1310-58-3 | Ceiling: 2 mg/m ³ | (vacated) Ceiling: 2 mg/m ³ | Ceiling: 2 mg/m ³ |
| 2-(2-butoxyethoxy)ethanol 112-34-5 | TWA: 10 ppm inhalable fraction and vapor | - | - |
| Phosphoric Acid 7664-38-2 | STEL: 3 mg/m ³ TWA: 1 mg/m ³ | TWA: 1 mg/m ³ (vacated) TWA: 1 mg/m ³ (vacated) STEL: 3 mg/m ³ | IDLH: 1000 mg/m ³ TWA: 1 mg/m ³ STEL: 3 mg/m ³ |
| Sodium Hydroxide 1310-73-2 | Ceiling: 2 mg/m ³ | TWA: 2 mg/m ³ (vacated) Ceiling: 2 mg/m ³ | IDLH: 10 mg/m ³ Ceiling: 2 mg/m ³ |

NIOSH IDLH *Immediately Dangerous to Life or Health*

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls

Showers, Eyewash stations & Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tight sealing safety goggles. Wear a face shield if splashing hazard exists.

Skin and body protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene

Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Avoid contact with skin, eyes or clothing. Take off all contaminated clothing and wash it before reuse. Wear suitable gloves and eye/face protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | |
|-----------------------|--------------------------|
| Physical state | Liquid |
| Appearance | Clear Yellow |
| Color | Yellow |
| Odor | Lemon |
| Odor threshold | No Information available |

| <u>Property</u> | <u>Values</u> | <u>Remarks • Method</u> |
|-------------------------------|--------------------------|-------------------------|
| pH | 13.5 - 14.5 | |
| Specific Gravity | 1.056 | |
| Viscosity | < 25 cP @ 25°C | |
| Melting point/freezing point | No Information available | |
| Flash point | None | |
| Boiling point / boiling range | | |
| Evaporation rate | No Information available | |
| Flammability (solid, gas) | No data available | |

| | |
|-----------------------------------|--------------------------|
| Flammability Limits in Air | |
| Upper flammability limit: | No Information available |
| Lower flammability limit: | No Information available |
| Vapor pressure | No Information available |
| Vapor density | No Information available |
| Water solubility | Complete |
| Partition coefficient | No Information available |
| Autoignition temperature | No Information available |
| Decomposition temperature | No Information available |

Other Information

| | |
|------------------------|------|
| Density Lbs/Gal | 8.80 |
| VOC Content (%) | 1 |

10. STABILITY AND REACTIVITY**Reactivity**

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Exposure to air or moisture over prolonged periods.

Incompatible materials

Strong acids. Aluminum. Incompatible with strong acids and bases. Incompatible with oxidizing agents.

Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating and toxic gases and vapors.

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure****Product Information**

The primary effects and toxicity of this material are due to its corrosive nature.

Inhalation

Avoid breathing vapors or mists. Inhalation of vapors in high concentration may cause severe irritation or burns to the respiratory tract.

Eye contact

Avoid contact with eyes. Corrosive. Causes severe eye damage.

Skin Contact

Avoid contact with skin. Corrosive. Contact with skin may cause severe irritation and burns.

Ingestion

Do not taste or swallow. Ingestion causes acute irritation and burns to the mucous membranes of the mouth, trachea, esophagus and stomach.

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|---------------------------------------|----------------------|-------------------------|-----------------|
| Potassium Hydroxide 1310-58-3 | = 284 mg/kg (Rat) | - | - |
| Tetrasodium EDTA 64-02-8 | = 1658 mg/kg (Rat) | - | - |
| 2-(2-butoxyethoxy)ethanol 112-34-5 | = 5660 mg/kg (Rat) | = 2700 mg/kg (Rabbit) | - |

Information on toxicological effects**Symptoms**

No Information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

| | |
|---------------------------------|--|
| Corrosivity | Causes burns. Extremely corrosive and destructive to tissue. Risk of serious damage to eyes. |
| Sensitization | No Information available. |
| Germ cell mutagenicity | No Information available. |
| Carcinogenicity | No Information available. |
| Reproductive toxicity | No Information available. |
| STOT - single exposure | No Information available. |
| STOT - repeated exposure | No Information available. |
| Chronic toxicity | Chronic exposure to corrosive fumes/gases may cause erosion of the teeth followed by jaw necrosis. Bronchial irritation with chronic cough and frequent attacks of pneumonia are common. Gastrointestinal disturbances may also be seen. Avoid repeated exposure. Possible risk of irreversible effects. |
| Target organ effects | EYES, Respiratory system, Skin. |
| Aspiration hazard | No Information available. |

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity 0.0633 % of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

| | |
|------------------------|-----------|
| ATEmix (oral) | 7,487.90 |
| ATEmix (dermal) | 35,797.00 |

12. ECOLOGICAL INFORMATION**Ecotoxicity**

0.0633% of the mixture consists of components(s) of unknown hazards to the aquatic environment

| Chemical Name | Algae/aquatic plants | Fish | Crustacea |
|--|---|--|---|
| Tetrasodium EDTA 64-02-8 | 1.01: 72 h Desmodesmus subspicatus mg/L EC50 | 41: 96 h Lepomis macrochirus mg/L LC50 static 59.8: 96 h Pimephales promelas mg/L LC50 static | - |
| 2-(2-butoxyethoxy)ethanol 112-34-5 | 100: 96 h Desmodesmus subspicatus mg/L EC50 | 1300: 96 h Lepomis macrochirus mg/L LC50 static | 100: 48 h Daphnia magna mg/L EC50 |
| Sodium Sulfate 7757-82-6 | - | 3040 - 4380: 96 h Lepomis macrochirus mg/L LC50 static 13500: 96 h Lepomis macrochirus mg/L LC50 13500 - 14500: 96 h Pimephales promelas mg/L LC50 6800: 96 h Pimephales promelas mg/L LC50 static | 2564: 48 h Daphnia magna mg/L EC50 630: 96 h Daphnia magna mg/L EC50 |
| Sodium Hydroxide 1310-73-2 | - | 45.4: 96 h Oncorhynchus mykiss mg/L LC50 static | - |
| Trisodium nitrilotriacetate 5064-31-3 | - | 175 - 225: 96 h Lepomis macrochirus mg/L LC50 static 560 - 1000: 96 h Oryzias latipes mg/L LC50 560 - 1000: 96 h Oryzias latipes mg/L LC50 semi-static 560 - 1000: 96 h Poecilia reticulata mg/L LC50 560 - 1000: 96 h Poecilia reticulata mg/L LC50 semi-static 72 - 133: 96 h Oncorhynchus mykiss mg/L LC50 static 93 - 170: 96 h Pimephales promelas mg/L LC50 flow-through 114: 96 h Pimephales promelas mg/L LC50 252: 96 h Lepomis macrochirus mg/L LC50 470: 96 h Pimephales promelas mg/L LC50 static | 560 - 1000: 48 h Daphnia magna mg/L LC50 |

Persistence and degradability

No Information available.

Bioaccumulation

Bioaccumulative potential.

| Chemical Name | Partition coefficient |
|----------------------------------|-----------------------|
| Potassium Hydroxide 1310-58-3 | 0.83 |

Other adverse effects No Information available**13. DISPOSAL CONSIDERATIONS****Waste treatment methods****Disposal of wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.**Contaminated packaging** Do not reuse container.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical Name | California Hazardous Waste Status |
|----------------------------------|-----------------------------------|
| Potassium Hydroxide 1310-58-3 | Toxic Corrosive |

14. TRANSPORT INFORMATION

The basic description below is specific to the container size. This information is provided for at a glance DOT information. Please refer to the container and/or shipping papers for the appropriate shipping description before tendering this material for shipment. For additional information, please contact the distributor listed in section 1 of this SDS.

DOT

UN/ID No. UN1760
Proper shipping name Corrosive liquids, n.o.s.
Hazard Class 8
Packing Group II
Special Provisions B2, IB2, T11, TP2, TP27
Description UN1760, Corrosive liquids, n.o.s. (contains Potassium Hydroxide), 8, II
Emergency Response Guide Number 154

TDG

UN/ID No. UN1760
Proper shipping name Corrosive liquids, n.o.s.
Hazard Class 8
Packing Group II
Description UN1760, Corrosive liquids, n.o.s. (contains Potassium Hydroxide), 8, II

15. REGULATORY INFORMATION

VOC CONTENT IS CARB EXEMPT AS LVP.

International Inventories

TSCA Complies
DSL/NDL Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical Name | SARA 313 - Threshold Values % |
|--------------------------------------|-------------------------------|
| 2-(2-butoxyethoxy)ethanol - 112-34-5 | 1.0 |

SARA 311/312 Hazard Categories

| | |
|-----------------------------------|-----|
| Acute health hazard | Yes |
| Chronic Health Hazard | Yes |
| Fire hazard | No |
| Sudden release of pressure hazard | No |
| Reactive Hazard | No |

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| Chemical Name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|----------------------------------|-----------------------------|------------------------|---------------------------|----------------------------|
| Potassium Hydroxide 1310-58-3 | 1000 lb | - | - | X |

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical Name | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ) |
|----------------------------------|--------------------------|----------------|---|
| Potassium Hydroxide 1310-58-3 | 1000 lb | - | RQ 1000 lb final RQ RQ 454 kg final RQ |

US State Regulations

California Proposition 65

WARNING: This product can expose you to chemicals including Ethylene Oxide, which is known to the state of California to cause cancer, or birth defects or other reproduction harm. For More Information go to www.P65Warnings.ca.gov.

U.S. State Right-to-Know Regulations

| Chemical Name | New Jersey | Massachusetts | Pennsylvania |
|--|------------|---------------|--------------|
| Potassium Hydroxide 1310-58-3 | X | X | X |
| 2-(2-butoxyethoxy)ethanol 112-34-5 | X | - | X |
| Sodium Sulfate 7757-82-6 | - | X | X |
| Phosphoric Acid 7664-38-2 | X | X | X |
| Sodium Hydroxide 1310-73-2 | X | X | X |
| Trisodium nitrilotriacetate 5064-31-3 | - | X | - |

U.S. EPA Label Information

EPA Pesticide Registration Number Not Applicable

16. OTHER INFORMATION

| | | | | |
|-------------|------------------|----------------|--------------------|------------------------------------|
| NFPA | Health hazards 3 | Flammability 0 | Instability 0 | Physical and Chemical Properties - |
| HMIS | Health hazards 3 | Flammability 0 | Physical hazards 0 | Personal protection D |

Issue Date 29-Nov-2022

Revision Date 29-Nov-2022

Revision Note

No Information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet