

Product Specifications

3M™ TopLine Autoscrubber Pad 5000

1.0 Product Description

This product is a floor maintenance pad used for cleaning floors prior to burnishing. The pad is made of high quality synthetic fibers in a non-woven web bonded with a durable resin system that permeates the entire pad. The pad is nominally one inch thick and is made in various sizes.

2.0 Intended Use

The pad is normally used on an automatic scrubber or rotary floor machine for cleaning finished floors prior to burnishing. The pad is used with neutral cleaners or as part of a system with TopLine Conditioner. When used as part of the TopLine System, the Autoscrubber pad and Conditioner are used to clean and condition the floor finish prior to burnishing with the Speed Burnish Pad.

3.0 Standard Sizes

Circular discs and other shapes are available in a variety of common sizes.

4.0 Color

Green/Amber

5.0 Requirements:

General Requirements:

This product shall be made of synthetic fibers and adhesives and shall not be significantly affected by water, detergents and cleaners normally used for floor maintenance. The product shall be reversible and nominally one inch thick.

Detailed Requirements

Typical Properties:

<u>Property</u>	<u>Value</u>	<u>Test Method</u>
O.D. Dimension	Designated size ± 1/16 inch	SB 61
Thickness	1 inch nominal	SB 66
Weight (4 in. x 6 in.)	18.1 g	
Fiber type	Proprietary synthetic mixture of sizes	
Average tensile strength	109 lbs./2 in.	SB 6.4
Wear (weight loss)	20%	SB 2.0
Recycle content of packaging	Not less than 35% post-consumer recycled material	

6.0 Packaging and Marking

Packaging: Circular pads:
13 inch through 24 inch – 5 pads per case
25 inch through 27 inch – 2 pads per case

Marking: Each carton shall be labeled to identify the contents by product name, size and manufacturer. Each pad shall be printed with manufacturer's name.

7.0 Pad Use and Cleaning

Directions for Use:

1. Dust mop
2. Scrub floor with TopLine Autoscrubber Pads under an automatic scrubber or rotary floor machine. Mop apply TopLine Conditioner properly diluted when using rotary machine. Apply conditioner through solution tank when using automatic scrubber.
3. Pick up solution with mop or scrubber vacuum.
4. Allow to dry
5. Burnish floor with TopLine Speed Burnish Pad.

Pad Cleaning:

Pads may be hosed out using a pressure spray nozzle to remove soil. Pads may be soaked in detergent or diluted stripping solution to dissolve caked-on soil or finish prior to cleaning.

Important Notice:

This flyer is intended to be an introductory summary. The information provided is based upon typical conditions and is believed to be reliable; however, due to the wide variety of intervening factors, 3M does not warrant that the results will necessarily be obtained. All details concerning product specifications and terms of sale are available from 3M.

3M
Building and Commercial Services Division

St. Paul, MN 55144-1000
1-800-852-9722

www.3M.com/commcare

3M is a trademark of 3M. © 3M 2007.