

Product Specifications

3M™ Eraser™ Burnish Pad 3600

1.0 Product Description

This product is a floor maintenance burnishing pad for use on ultra high speed floor machines that operate in the range of 1500-3000 rpm. The pad is made of high quality synthetic fibers in a non-woven web bonded with a durable resin system that permeates the entire pad. The pad is nominally one inch thick and available in various sizes.

2.0 Intended Use

The pad is used on cord electric, battery electric or propane powered floor machines for burnishing 3M floor finished. Also designed for use on other finishes resistant to degradation from burnishing.

3.0 Standard Sizes

Circular discs and other shapes are available in a variety of common sizes.

4.0 Color

Pink

5.0 Requirements:

General Requirements:

This product shall be made of synthetic fibers and shall not be significantly affected by water, detergents and cleaners normally used for floor maintenance. The product shall be reversible and nominally inch thick.

5.0 Requirements (continued)

Detailed Requirements Typical Properties:		
<u>Property</u>	<u>Value</u>	<u>Test Method</u>
O.D. Dimension	Designated size ± 1/16 inch	SB 61
Thickness	1 inch nominal	SB 66
Weight (4 in. x 6 in.)	16.2 g	
Fiber type	Proprietary synthetic mixture of sizes	
Average tensile strength	100 lbs./2 in.	SB 6.4
Recycle content of packaging	Not less than 35% post-consumer recycled material	

6.0 Packaging and Marking

Packaging: 5 pads per case

Marking: Each carton shall be labeled to identify the contents by product name, size and manufacturer. Each pad shall be printed with manufacturer's name.

7.0 Pad Use and Cleaning

Directions for Use:

Dust mop or sweep floors prior to scrubbing. Pick up scrubbing or cleaning solution with a mop, wet vacuum or automatic scrubber. Rinse floor and let dry prior to recoating or opening to traffic.

Pad Cleaning:

Pads may be hosed out using a pressure spray nozzle to remove soil. Pads may be soaked in detergent or diluted stripping solution to dissolve caked on soil or finish prior to hosing out.

Important Notice:

This flyer is intended to be an introductory summary. The information provided is based upon typical conditions and is believed to be reliable; however, due to the wide variety of intervening factors, 3M does not warrant that the results will necessarily be obtained. All details concerning product specifications and terms of sale are available from 3M.

3M
Building and Commercial Services Division

St. Paul, MN 55144-1000

1-800-852-9722

www.3M.com/commcare

3M and Eraser are trademarks of 3M.

©3M 2007