Adfinity™ 20D / X20D / X20C / X24D Available with EcoFlex™ System

Walk-Behind Scrubbers



FACT SHEET



Traction Drive For Increased Productivity.

The new line of Adfinity™ traction-drive scrubbers from Advance offers multiple versions to choose from for the scrubber size and performance you need. With scrub paths ranging from 20 to 24 inches wide, most of these high-feature models are available with an onboard detergent dispensing system, for the highest level of cleaning productivity.

If you're looking for a scrubber that offers the most efficient use of cleaning chemicals, an Adfinity model with EcoFlex™ is your answer. Advance's patented EcoFlex onboard detergent dispensing system eliminates guesswork by dispensing detergent at the manufacturer's recommended dilution ratio. Adfinity models with EcoFlex eliminate premixing of chemicals, which saves time and prevents detergent and water waste. Multiple pad pressure settings on select models help to maximize run time, yet still offer more pressure when cleaning highly-soiled areas. All Adfinity machines come standard with an onboard battery charger, allowing the flexibility to charge the machine at any available electrical outlet.

One-Touch™ operation makes the Adfinity line of scrubbers easy to learn and easy to use. Features not offered on other small disc scrubbers, include Advance's unique "click on" brushes for fast and easy changeovers. Adfinity drive models are equipped with forward and reverse traction drive and an ergonomic and safe paddle design for extra operator comfort. All Adfinity scrubber models are designed for easy access to the battery, detergent dispensing system, where applicable, and the recovery tank.

Adfinity scrubbers are a great addition to any green cleaning program. Operating at a sound level of only 65 dB A, this machine is well below the requirements for sound level set by LEED-EB and GS-42 − making Adfinity ideal for daytime cleaning in any facility. This line of scrubbers also features Smart Solutions™ flow rate, which is engineered to provide effective cleaning, and the longest run time (over 1.5 hours) on the floor between dump and refills. This saves water and costly chemicals, while increasing productivity. The Adfinity X20D and X24D disc models have received NFSI certification for reducing the possibility of slip-and-fall accidents.

STANDARD FEATURES INCLUDE

- Smart Solutions™ Flow Rate
- EcoFlex™ Onboard Detergent Dispensing System (X20D, X20C, X24D)
- Onboard Battery Charger
- Variable Pad Pressure
- Interchangeable Scrub Decks
- Tools-free removal of squeegee and squeegee blades

OPTIONAL ACCESSORIES INCLUDE

- Variety of Scrub Brushes
- 20 inch Disc Deck Kit
- Polyurethane Squeegee Blades
- 20 inch Cylindrical Deck Kit
- Integrated Solution Fill Hose
- 24 inch Disc Deck Kit
- Hour Meter Kit
- Wet Pick-up Wand Kit
- Scrub and Vac Kit

TYPICAL APPLICATIONS INCLUDE

- Hospitals / Healthcare Facilities
- Schools and Universities
- Churches and Religious Facilities
- Hotels
- Commercial Cleaning
- Manufacturing Facilities
- Distribution / Warehouse
- Government Buildings and Installations
- Airports, Train Stations, Bus Depots
- Casinos
- Office Buildings
- Health Clubs



Advance Adfinity[™] Available with EcoFlex[™] System

Automatic Scrubbers



A wrap-around safe paddle system makes it easier to control and maneuver the machine.



Tools-free removable brushes can be easily changed.



Easy access rear-port features include the solution tank fill, a large recovery drain hose with pinch-flow regulation, and the solution drain hose which also functions as a solution level indicator.



Defining Cleaning Innovation...

- Our products are designed using innovative technology that increases productivity and drives down the cost to clean.
- You can get expert service and maintenance for your Advance machines from factorytrained personnel around the world. Fast parts delivery, too.
- Maintain peak performance with Nilfisk Genuine OEM Parts.

Nilfisk Genuine OEM Parts

Technical Specifications

| Models | Adfinity™ 20D | Adfinity™ X20D | Adfinity™ X20C | Adfinity™ X24D |
|-----------------------------|---|--|--|--|
| Scrub Head Type | Disc | Disc | Cylindrical with debris hopper | Disc |
| Deck Interchangeability | All deck types interchangeable – ALL MODELS | | | |
| Scrub Path | 20 in (50.8 cm) pad holder standard; brushes available – 20D and X20D | | Dual 20 in (50.8 cm) cylindrical brush system | (2) 12 in (30.5 cm) pad holders standard; brushes available |
| Drive System | 0.3 hp (200 W) variable forward Max speed 3.5 mph (5.6 km/hr), | | | |
| Max Productivity | 26,400 ft ² (2,453 m ²) | 26,400 ft ² (2,453 m ²) | 26,400 ft ² (2,453 m ²) | 31,680 ft ² (2,943 m ²) |
| @ 3.0 mph (4.8 km/hr) | | | | |
| Scrub Pressure (2 settings) | | | | |
| Floating | 50 lb (25 kg) | 50 lb (25 kg) | 57 lb (26 kg) | 61 lb (28 kg) |
| Locked | 70 lb (32 kg) | 70 lb (32 kg | _ | _ |
| Scrub Head Speed | 170 rpm | 170 rpm | 570 rpm | 230 rpm |
| EcoFlex™ System Available | NA | Yes | Yes | Yes |
| Solution Flow Rates | | | | |
| Smart Solutions™ | 0.15 gal/min (0.55 L/min) | | | |
| variable up to | 0.3 gal/min (1.1 L/min) – ALL MODELS | | | |
| Squeegee Width | 29.9 in (75.9 cm) | 29.9 in (75.9 cm) | 29.9 in (75.9 cm) | 31.9 in (81.0 cm) |
| Dimensions (w/o squeegee) | L = 52 in (132 cm) | L = 52 in (132 cm) | L = 49.2 in (125 cm) | L = 51.6 in (131 cm) |
| | W = 21.3 in (54 cm) | W = 21.3 in (54 cm) | W = 22.4 in (57 cm) | W = 25.6 in (65 cm) |
| | H = 42.9 in (109 cm) | H = 42.9 in (109 cm) | H = 42.9 in (109 cm) | H = 42.9 in (109 cm) |
| Weights | | | | |
| Without batteries | 240 lb (109 kg) | 244 lb (111 kg) | 247 lb (112 kg) | 243 lb (110 kg) |
| With batteries | 346 lb (157 kg) | 350 lb (159 kg) | 362 lb (164 kg) | 374 lb (170 kg) |
| Voltage | 24 V – ALL MODELS | | | |
| Power Source | (2) 12 V batteries (wet-acid and maintenance free available) – ALL MODELS | | | |
| Onboard Battery Charger | 24 V wet/maintenance free compatible – ALL MODELS | | | |
| Solution Tank | 14.5 gal (55 L) – ALL MODELS | | | |
| Recovery Tank | 14.5 gal (55 L) – ALL MODELS | | | |
| Scrub Motor(s) | 0.65 hp (480 W) | 0.65 hp (480 W) | (2) 0.54 hp (400 W) | (2) 0.47 hp (350 W) |
| Vacuum Motor | 0.44 hp (330 W) – ALL MODELS | | | |
| Sound Level | 65.8 dB A at operator's position – ALL MODELS | | | |
| Approvals | ETL, CSA, CE – ALL MODELS | | | |
| Certification | - | NFSI | - | NFSI |
| Part Number | 56317327 w/130 Ah wet-acid batt. 56317328 w/98 Ah gel batt. | 56317329 w/130 Ah wet-acid batt. 56317330 w/98 Ah gel batt. | 56317331 w/130 Ah wet-acid batt. 56317332 w/98 Ah gel batt. | 56317333 w/130 Ah wet-acid batt. 56317334 w/98 Ah gel batt. |

Specifications are subject to change without notice.



14600 21st Avenue North Plymouth, MN 55447-3408 www.advance-us.com

www.advance-us.com
Phone: 800-850-5559
Fax: 800-989-6566

240 Superior Boulevard Mississauga, Ontario, Canada L5T 2L2 www.nilfisk-advance.ca

Phone: 905-564-1149 or 800-668-8400 Fax: 905-564-1030 or 800-263-5111



NFSI (II) (II) (II) (II)

