

## ***MicroMag - Brush Assist***

Micro 17"

### **GENERAL**

Machine shall be of the type generally described as a battery-powered "automatic":

Tomcat

The specific model and size should be:

Micro 17"-D

This bid defines a self-propelled via pad assist machine that wet "scrubs and dry" vacuums a path of:

17"

For expedited parts delivery, machine shall be made in:

United States

The machine contains separate tanks for solution and recovery water, with a minimum capacity in each tank of:

10 gallons

### **SOLUTION TANK**

The solution tank shall be made of heavy gage (.3125") polyethylene plastic. Dual fill ports, with one at the front of the machine and a second at the rear. Solution screen must be stainless steel and located, with the check valve, on the scrub deck permitting top access. The solution tank specifically must hold a minimum of:

10 gallons

### **RECOVERY TANK**

Recovery tank shall be made of polyethylene, that is a minimum thickness of (.3125"). Tank shall be designed to be easy to clean, with complete access to the recovery tank's floor, wherein the entire inside and floor of the tank is visible and reachable. A heavy duty, discharge control, 1.5" diameter drain hose shall be supplied, made of latex rubber. To simplify access for planned maintenance, tank must include:

"Tip Back" feature

Recovery tank must include "Drain Saver" basket, to collect all liter in the recovery water, to keep discharge water from clogging floor drains. Drain saver basket must be constructed of stainless steel, with 1/4" mesh screen, and be removed without tools or loose fasteners. Tank Capacity of:

10 gallons

### **BRUSHES/PADS**

For preferred maneuverability and productivity the machine shall use:

1 disk brush

Scrub brushes shall be:

Qty: 1 @ 17"

For preferred cleaning performance the machine's scrub brushes should operate at:

270 rpm

### **BRUSH HEAD**

To reduce the stress on the operator, the machine's brush head shall be raised and lowered by an electric actuator with a minimum capacity of:

250 lbs

### **BRUSH MOTOR**

The scrub motor shall be heavy duty, permanent-magnet DC:

(Qty: 1) .75 hp / 200 rpm

### **VACUUM MOTOR**

The vacuum motor is to be protected with a ball and stainless screen system wherein the ball reacts to the level of foam inside the tank and shuts off air flow to the vacuum motor. The vacuum motor must be 3-stage and rated at:

650 watts

### **SQUEEGEE**

Squeegee shall be curved, with four usable edges on the rear blade. It shall move when the machine turns to control water. It shall be protected against impact with "Non-Marking" 4" diameter, side wheels, and a breakaway feature. For preferred water recovery, the squeegee shall have a minimum width of:

26"

### **DRIVE SYSTEM**

Machine shall have an adjustable pad assist system, which maintains a level scrub deck at all times. The adjustable pad bias shall be done via a wheel that applies pressure to the outside of the brush block. Pad or Brush drive must be fully:

Adjustable

**TIRES / CASTERS**

For preferred machine stability, only machines with a 4-point stance will be acceptable. Machines with 3-point stance will not be considered.

Front casters shall be solid, non-marking and size minimum of:

4-Point Stance

Qty 2: 2.5" dia x 1.5" wide

Rear wheels shall be solid, low rolling resistant, non-marking and size minimum of:

Qty 2: 8" dia x 1.5" wide

**BATTERIES**

Scrubber shall include at least 2 batteries, to form a minimum of 24-volt DC system. Batteries must be located in a 12" tall, plastic battery tray to contain any and all fluids. The battery size must be a minimum of:

85 ah

For extended run time, optional battery upgrade should be quoted in the size of:

130 ah

**CHARGER**

Charger shall be "shelf mounted", and fully automatic type, running on 110-volt / 60-Hz / AC power. It shall provide a minimum of 24-volt DC output of:

8 amps

**CONTROLS**

A switch control system, arranged to allow operator to engage forward speed with the finger. Twist grip controls which govern direction change along speed, will not be considered.

The instrument panel shall include a Brush Pressure Gauge, a Battery gauge and Hour meter.

The squeegee shall be lifted and lowered by a simple lever, with the vacuum automatically operating whenever the squeegee is lowered. To more completely dry the squeegee hose, and reduce discharge back onto the floor, the hose will have a trap.

**DIMENSIONS**

Machine maximum dimensions shall be:

(36"L x 19"W x 39"H)

Machines maximum weight (including batteries) shall be:

326 pounds

**CONSTRUCTION**

For preferred durability and longevity the scrubber's main frame shall be made of a steel, powder-painted to resist corrosion, and of a thickness of at least:

10-gage (1/8")

This heavy gage frame shall fully support the weight of the batteries, the tanks, hold the scrub deck rigid and

locate the casters and transaxle. For future ease of service, all of the fasteners on the scrubber shall be made of:

Stainless Steel

No machine with casters or transaxle mounts that bolt directly to the tanks will be acceptable.

**OTHER FEATURES / OPTIONS**

Non-Marking Tires

Standard

E-Stop

Optional

Remote Spray Hose

Optional

Vacuum Wand

Optional

Sealed Batteries

Optional

Onboard Charger

Optional

Stainless Steel Baffle

Optional

Parking Brake

Optional

HD 1.0hp Motor

Optional