

# EXHAUST HOODS

## Tools Needed

- Properly Equipped Dilution Center
- Properly Prepared 3-Compartment Sink
- Clean Towels
- Utility Bucket
- Non-Abrasive Pad
- Eye Protection
- Safety Stool


## Product Needed

Spic and Span® Floor Cleaner




**FREQUENCY OF CLEANING:** *Nightly.*

**SPECIAL DIRECTIONS FOR THIS TASK:** *Wear eye protection. If sensitivity to cleaning solutions is a concern, wear disposable gloves.*



### STEP 1

- Fill a clean utility bucket with a warm solution of floor cleaner from the Dilution Center.



### STEP 2

- Turn off exhaust hood, if applicable.




### STEP 3

- Dip non-abrasive pad into the cleaning solution.
- Scrub interior and exterior of exhaust hood with non-abrasive pad, a small section at a time.



### STEP 4


- Use clean towels to wipe each section clean and dry.



### STEP 5


- Dip non-abrasive pad in cleaning solution, and wipe down Ansul pipes.

**CAUTION:** *Be careful not to trip Ansul Fire System.*




### STEP 6

- Use clean towels to wipe pipes clean and dry.




### STEP 7

- Remove light shields and cages.
- Wash and rinse the light shields/cages in the 3-compartment sink.
- Allow to air-dry.



### STEP 8

- When they are dry, return light shields and cages to their proper locations.



### STEP 9

- Check for any loose paint, chipped glass, or burnt-out lights; report to manager.



### STEP 10

- If used, remove and discard disposable gloves.
- Wash hands before returning to service area.